

DESIGN GUIDE

Passenger Car Tyres

| INDEX | PAGE |
|---|----------------|
| SUMMARY OF THE MAIN CHANGES REGARDING PASSENGER CAR TYRES | PC.2 |
| CALCULATION OF TYRE DIMENSIONS | PC.3 |
| GUIDELINES FOR CODE DESIGNATED RIM WIDTHS AND RIM WIDTH FOR CALCULATION OF TYRE DIMENSIONS | PC.4 |
| STATIC ENVELOPE CONTOUR | PC.5 to PC.7 |
| THEORETICAL ROLLING CIRCUMFERENCE | PC.8 |
| THEORETICAL STATIC LOADED RADIUS | PC.8 |
| DIMENSIONAL GUIDELINES FOR FUTURE SERIES | |
| Series '80' to '75' | PC.9 |
| '70' to '65' | PC.10 |
| '60' to '55' | PC.11 |
| '50' to '45' | PC.12 |
| '40' to '35' | PC.13 |
| '30', '25' and '20' | PC.14 |
| DIMENSIONAL GUIDELINES FOR T TYPE TEMPORARY-USE SPARE TYRES | |
| Metric Designation — Radial, Diagonal and Bias Belted | |
| Series '95' to '90' | PC.15 |
| Series '85' to '80' | PC.16 |
| Series '75' to '70' | PC.17 |
| Series '65' to '60' | PC.18 |
| Series '55' to '50' | PC.19 |
| SERVICE CONDITIONS | |
| Aim – Definitions | PC.20 |
| Formulae | PC.20 to PC.22 |
| Service Conditions | PC.23 |
| GUIDELINES ON HARMONISATION OF LOAD CAPACITIES | |
| Load indices for future standardization | PC.24 to PC.45 |